

# Connection Change Request

**POST** `/:site_number/connections`

Post a new change request to close, modify, reassign, or create an outreach connection.

## Example

[https://secure.accesssacs.com/api\\_accesssacs\\_mobile/v2/12345/connections](https://secure.accesssacs.com/api_accesssacs_mobile/v2/12345/connections)

---

```
{
  "ConnectionId": -1,
  "Complete": false,
  "ConnectionDate": "06/05/2015",
  "ConnectionTypeId": 1,
  "FamilyConnection": false,
  "ContactIndvId": 76,
  "OpenCategoryId": 1,
  "Reassign": false,
  "NewCallerIndvId": -1,
  "NewTeamId": 1,
  "Comment": "Test",
  "ResponseIdList": [-1]
}
```

## Required Permissions

The user must fall into one of the categories below:

- System Administration
- A user with the following rights:
  - Ability to create a change request
  - Full Rights to at least one Connection Type
  - Ability to locate a person or search for a member
  - Full rights to Add/View Comments

## Request Header

Basic Authorization is used to determine security rights for the user credentials supplied using the following parameters.

**u sername** : "jadams"

**password** : "password231"

## URL Parameters

**Site\_number** – Site number to gather data for.

**Individual\_ID** – Individual associated with the record. Values from [Individual Search API](#).

## JSON Body Text

```
ConnectionId: [-1] **
Complete: [ true | false] Connection completed?
ConnectionDate: "06/05/2015" format MM/DD/YYYY
ConnectionTypeId: 1 Values from Connection Types API
FamilyConnection: [ true | false] Family connection vs. Individual connection.
ContactIndvId: 76 Who will be contacted? Values from Individual Search API
OpenCategoryId: 1 *Not using, default to 1
Reassign: [ true | false] True means the connection will be reassigned; False means it will not.
NewCallerIndvId: -1 Who will be contacting the individual? Values from Individual Search API.
NewTeamId: 1 ID of team who will be contacting the individual. Values from Connections Team List. ***
Comment: "Test" This is a comment concerning the connection.
ResponseIdList: [-1] Values from Available Responses API. (You will need to use the ConnectionTypeId from the
Connection Types API in order to run the Available Responses API.) ****
```

\*\* Values for ConnectionID :

Add New : -1

Complete/Modify/Reassign : Enter Connection Id. Value from Connection Details API.

\*\*\* Either an Individual or Team can be assigned to make the connection. If a team will be making the connection, then the NewCallerIndvid will have a value of -1. If an individual will be making the connection, then the NewTeamId will have a value of -1.

\*\*\*\* Valid Values for ResponseldList:

No responses: -1

Responses Provided: Enter them in the following format: [value 1, value 2, value 3...]

## Return Data

```
HTTP 200 OK
The Id returned is the Connection Change Request ID (ConnectionCRId).
```

## Notes

When adding a new connection, these fields must be provided:

- ConnectionId
- Complete
- ConnectionDate
- ConnectionTypeId
- FamilyConnection
- ContactIndvId
- Reassign
- NewCallerIndvId
- NewTeamId
- Comment
- ResponseldList

When reassigning a connection, these fields must be provided:

- ConnectionId
- Complete
- ConnectionDate
- Reassign
- NewCallerIndvId
- NewTeamId
- Comment
- ResponseldList